

P-Channel Logic Level Enhancement Mode Field Effect Transistor


Product Summary:

BV <sub>DSS</sub>	-20V
R <sub>DS(on)</sub> (MAX.)	44mΩ
I <sub>D</sub>	-12A

P-Channel MOSFET

UIS, R<sub>g</sub> 100% Tested

Pb-Free Lead Plating & Halogen Free



ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNIT
Gate-Source Voltage		V <sub>GS</sub>	±12	V
Continuous Drain Current	T <sub>C</sub> = 25 °C	I <sub>D</sub>	-12	A
	T <sub>A</sub> = 25 °C		-6	
	T <sub>C</sub> = 100 °C		-8	
Pulsed Drain Current <sup>1</sup>		I <sub>DM</sub>	-48	
Power Dissipation	T <sub>C</sub> = 25 °C	P <sub>D</sub>	21	W
	T <sub>C</sub> = 100 °C		8.3	
Power Dissipation	T <sub>A</sub> = 25 °C	P <sub>D</sub>	2.5	W
	T <sub>A</sub> = 70 °C		1.6	
Operating Junction & Storage Temperature Range		T <sub>J</sub> , T <sub>stg</sub>	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to-Case	R <sub>θJC</sub>		6	°C / W
Junction-to-Ambient <sup>3</sup>	R <sub>θJA</sub>		50	

<sup>1</sup>Pulse width limited by maximum junction temperature.

<sup>2</sup>Duty cycle ≤ 1%

<sup>3</sup>50°C / W when mounted on a 1 in<sup>2</sup> pad of 2 oz copper.



ELECTRICAL CHARACTERISTICS ( $T_J = 25\text{ }^\circ\text{C}$ , Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
<b>STATIC</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-0.3	-0.75	-1.2	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 12V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -16V, V_{GS} = 0V$			-1	$\mu A$
		$V_{DS} = -16V, V_{GS} = 0V, T_J = 125\text{ }^\circ\text{C}$			-10	
On-State Drain Current <sup>1</sup>	$I_{D(ON)}$	$V_{DS} = -5V, V_{GS} = -4.5V$	-12			A
Drain-Source On-State Resistance <sup>1</sup>	$R_{DS(ON)}$	$V_{GS} = -4.5V, I_D = -5A$		37	44	m $\Omega$
		$V_{GS} = -2.5V, I_D = -4A$		55	70	
		$V_{GS} = -1.8V, I_D = -1A$		65	90	
Forward Transconductance <sup>1</sup>	$g_{fs}$	$V_{DS} = -5V, I_D = -4A$		14		S
<b>DYNAMIC</b>						
Input Capacitance	$C_{iss}$	$V_{GS} = 0V, V_{DS} = -10V, f = 1MHz$		679		pF
Output Capacitance	$C_{oss}$			124		
Reverse Transfer Capacitance	$C_{rss}$			106		
Total Gate Charge <sup>1,2</sup>	$Q_g$	$V_{DS} = -10V, V_{GS} = -4.5V, I_D = -4A$		12.8		nC
Gate-Source Charge <sup>1,2</sup>	$Q_{gs}$			2.2		
Gate-Drain Charge <sup>1,2</sup>	$Q_{gd}$			4.1		
Turn-On Delay Time <sup>1,2</sup>	$t_{d(on)}$	$V_{DS} = -10V, I_D = -1A, V_{GS} = -4.5V, R_{GS} = 6\Omega$		10		nS
Rise Time <sup>1,2</sup>	$t_r$			18		
Turn-Off Delay Time <sup>1,2</sup>	$t_{d(off)}$			32		
Fall Time <sup>1,2</sup>	$t_f$			22		
<b>SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (<math>T_C = 25\text{ }^\circ\text{C}</math>)</b>						
Continuous Current	$I_S$				-12	A
Pulsed Current <sup>3</sup>	$I_{SM}$				-48	
Forward Voltage <sup>1</sup>	$V_{SD}$	$I_F = -5A, V_{GS} = 0V$			-1.2	V

<sup>1</sup>Pulse test : Pulse Width  $\leq 300\ \mu\text{sec}$ , Duty Cycle  $\leq 2\%$ .







<sup>2</sup>Independent of operating temperature.





<sup>3</sup>Pulse width limited by maximum junction temperature.

EMC will review datasheet by quarter, and update new version.



TYPICAL CHARACTERISTICS





Ordering & Marking Information:

Device Name: EMF44P02V for EDFN 3 x 3



F44P02: Device Name

ABCDEFG: Date Code


A: Assembly House

B: Year(A:2008 B:2009 C:2010....)

C: Month(A:01 B:02 C:03 D:04 E:05 F:06 G:07 H:08 I:09 J:10 K:11 L:12)

DEFG: Serial No.


Outline Drawing



Dimension in mm


Dimension	A	A1	b	c	D	D1	E	E1	E2	e	L	L1	$\theta 1$
Min.	0.65	0	0.20	0.10	2.90	2.15	3.10	2.90	1.53	0.55	0.25	-	0°
Typ.	0.75	-	0.30	0.15	3.00	2.45	3.20	3.00	1.97	0.65	0.40	0.075	10°
Max.	0.90	0.05	0.40	0.25	3.30	2.74	3.50	3.30	2.59	0.75	0.60	0.150	14°

Recommended minimum pads





Tape&Reel Information: 5000pcs/Reel



產品別	EDFN3X3
Reel 尺寸	13"
編帶方式	<p>FEEED DIRECTION</p>
前空格	50
後空格	50
裝箱數	
滿捲數量	5K
捲/內盒比	1 : 1
內盒滿箱數	5K
內/外箱比	10 : 1
外箱滿箱數	50K